




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>3</sup> : <b>A61L 2/10, A61M 31/00</b>	<b>A1</b>	(11) International Publication Number: <b>WO 85/ 00979</b> (43) International Publication Date: <b>14 March 1985 (14.03.85)</b>
(21) International Application Number: <b>PCT/US84/00929</b> (22) International Filing Date: <b>15 June 1984 (15.06.84)</b> (31) Priority Application Numbers: <b>524,704 548,389</b> (32) Priority Dates: <b>19 August 1983 (19.08.83) 3 November 1983 (03.11.83)</b> (33) Priority Country: <b>US</b> (71) Applicant: <b>BAXTER TRAVENOL LABORATORIES, INC. [US/US]; One Baxter Parkway, Deerfield, IL 60015 (US).</b> (72) Inventors: <b>KULIN, Daniel ; 1700 Busse Road, Maren-go, IL 60052 (US). GRANZOW, Daniel, B. ; 33666 N. Oak Drive, Ingleside, IL 60041 (US). DANIELSEN, Brant, R. ; 1009 N. Clarendon Drive, Round Lake Beach, IL 60073 (US). MUNSCH, John, M. ; 912 Wexford Court, Libertyville, IL 60048 (US). BEL-LOTTI, Marc ; 1215 Willow Road, Winnetka, IL 60093 (US). TAYLOR, Larry, C.; 5421 Shore Drive, McHenry, IL 60050 (US).</b>	(74) Agents: <b>ELLIS, Garretson et al.; One Baxter Parkway, Deerfield, IL 60015 (US).</b> (81) Designated States: <b>BE (European patent), CH (Euro-pean patent), DE (European patent), FR (European patent), GB (European patent), JP, NL (European patent), SE (European patent).</b> Published <i>With international search report.</i>	

(54) Title: DEVICE FOR PROVIDING ANTIBACTERIAL RADIATION



## (57) Abstract

An apparatus for automatically connecting and disconnecting a pair of connectors (20, 22) includes first and second relatively movable means (34, 40) to carry the connectors and to move them back and forth between connected and disconnected positions. Rack and gear means (42, 44) may be used having a variable mechanical advantage at different positions to facilitate connection and disconnection of the connectors. The apparatus may also have means (16) for providing radiation for antibacterial effect on the connectors, typically ultraviolet radiation.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	KR	Republic of Korea
AU	Australia	LI	Liechtenstein
BE	Belgium	LK	Sri Lanka
BG	Bulgaria	LU	Luxembourg
BR	Brazil	MC	Monaco
CF	Central African Republic	MG	Madagascar
CG	Congo	MR	Mauritania
CH	Switzerland	MW	Malawi
CM	Cameroon	NL	Netherlands
DE	Germany, Federal Republic of	NO	Norway
DK	Denmark	RO	Romania
FI	Finland	SD	Sudan
FR	France	SE	Sweden
GA	Gabon	SN	Senegal
GB	United Kingdom	SU	Soviet Union
HU	Hungary	TD	Chad
JP	Japan	TG	Togo
KP	Democratic People's Republic of Korea	US	United States of America

DEVICE FOR PROVIDING ANTIBACTERIAL RADIATION5     Technical Field and Prior Art

          In various fields of medicine and elsewhere, and particularly in continuous ambulatory peritoneal dialysis (CAPD) there is a need to make and break connections between peritoneal  
10     tubing communicating with the peritoneal cavity and a source of peritoneal dialysis solution with substantially sterile procedure. At the same time it is desirable for patients undergoing CAPD or another form of peritoneal dialysis on a  
15     chronic basis to be released from close supervision by medical personnel and permitted to do the dialysis solution exchange procedures independently at their homes or places of work. However, the need for maintenance of substantially sterile  
20     procedure remains critical if peritonitis is to be avoided, particularly in the case of patients on CAPD.

          In response to this, various systems for irradiation of connectors have been proposed, and one has been commercially  
25     developed, in which at least the outer connector is made of ultraviolet transparent material, and after the connectors are brought together but before seals are released to permit flow of solution through the newly formed connection, the connectors are  
30     irradiated with ultraviolet light for antibacterial effect outside and inside the connectors. See Popovich and Moncrief Patent Application Serial No. 270,800, filed June 5, 1981, entitled "PERITONEAL DIALYSIS METHOD"; Kulin et al. U.S. Patent  
35     No. 4,412,834, entitled "ANTIMICROBIAL ULTRAVIOLET IRRADIATION OF CONNECTOR FOR CONTINUOUS AMBULATORY PERITONEAL DIALYSIS"; and Hogan U.S. Patent No. 4,433,244, entitled "APPARATUS FOR IRRADIATING TUBING CONNECTORS. In all of the above references,  
40     ultraviolet radiation is used for antibacterial effect in the newly formed connection.



5 Patients who are undergoing peritoneal dialysis on a chronic  
basis are often elderly, ill, and debilitated. The disease  
which requires their life maintenance by dialysis interferes  
with nerve conductivity which, in turn, reduces their manual  
10 dexterity. Accordingly, it becomes desirable in the case of  
many patients to provide them with all assistance possible in  
the making and breaking of connections during peritoneal  
dialysis and particularly CAPD operations.

15 In response to this, automatic systems for making and  
breaking connections have been provided. For example, the  
Steri-Track device which has been used and which is described in  
an article entitled "CAPD For the Blind" from the periodical  
20 Nephrology Nurse, March/April, 1981, pp. 53-54. This device is  
a self-contained portable device. When doing bag exchanges, a  
fresh bag of dialyzate is placed into a stationary end of a  
holder. At this point the protective tab of the bag is removed,  
25 and a spike is taken from the discharge bag and fitted into the  
grooves of a sliding plate. The patient now manipulates the  
sliding plate toward the bag with the result that the spike will  
plunge into the port of the bag with alleged 98 percent  
30 probability.

Also, Munsch et al. Patent Application No. 416,785, filed  
September 10, 1982, shows an improved device for automatic  
connection and disconnection of connectors in CAPD and the like.

35 In accordance with this invention, an automatic connection  
and disconnection system is provided, preferably in conjunction  
with a radiation system for exerting antibacterial effect on  
connectors before or after joining, in a peritoneal dialysis  
system or other system as may be desired. By this invention a  
40 variable mechanical advantage advancement system of the first  
and second means that carry the respective connectors is  
provided so that, preferably, even a debilitated person can



5 exert the amount of force necessary to make and break the connection between the connectors, while at the same time the connectors can be separated by a desired substantial distance with a simple short motion of the handle.

10 This and other advantages and features are more fully described in the description below.

#### Description of the Invention

15 In accordance with this invention apparatus for automatically connecting and disconnecting a pair of connectors is provided. The apparatus includes first and second means for respectively holding the connectors, the first and second means being relatively movable between first and second positions, to  
20 cause connectors carried in the first and second means to be separated from each other in the first position, and to cause the carried connectors to be joined together in the second position. Typically, the relatively movable relationship of the  
25 first and second means is accomplished by having the first means stationary and the second means movable. However, the converse may be true and, if desired, both of the means may be movable.

30 The first and second means can respectively hold the connectors within a housing, and means can be present within the housing for providing antibacterial radiation, for example ultraviolet light. Also, the housing defines drawer means, the drawer means carrying the first and second means for holding the  
35 connectors, to permit exposure of the connectors to antibacterial radiation when the drawer means is closed, but to permit manual access to the connectors when the drawer means is opened.



5 Rack and gear means can be provided for relatively moving  
the first and second means between the first and second  
positions. The gear of the rack and gear means defines gear  
teeth of increasing pitch, i.e., distance of the center point of  
10 each gear tooth from the gear's center of rotation. This  
increasing pitch relationship is defined about at least a  
portion of the periphery of the gear. The rack of the rack and  
gear means defines mating teeth correspondingly spaced along its  
15 length in positions to permit relatively linear motion between  
the rack and gear as the gear rolls along the rack. As the  
result of this, the mechanical advantage of the rack and gear  
means varies with the position of the gear along the rack  
20 because of the varying pitch of the gear teeth. Preferably, the  
mechanical advantage is substantially at a maximum when the rack  
and gear means are at the second position.

In other words, the gear teeth which engage the teeth of the  
25 rack at the second position are of minimum pitch, i.e., their  
distance to the center of rotation is minimum, resulting in the  
highest mechanical advantage in the system. Accordingly, it  
becomes easier for anybody including debilitated patients to  
30 make or break a tight, frictional connection or disconnection,  
assisted by the increased mechanical advantage of the rack and  
gear means at this second position, which corresponds to the  
connected position of the connectors.

35 However, as the connectors are pulled apart, the mechanical  
advantage decreases as the gear moves along the rack, with teeth  
of increasing pitch being in contact with the rack.  
Accordingly, after the original, tight, frictional connection  
40 between the connectors is broken, the mechanical advantage is  
reduced, causing the rack to move faster as the gear rotates at  
a constant rate.

5           Thus, the simple operation of the handle to disconnect the connectors results in an initial, high mechanical advantage for breaking the connection, and then a reduced mechanical advantage to cause the connectors to thereafter move apart more rapidly, for less required motion of the handle.

10           It is generally preferred for the handle attached to the gear to be rotatable only about 180° which, because of the variable mechanical advantage system of this invention, is  
15   sufficient to permit the first and second means to be spaced far enough apart to sufficiently space the connectors carried in the first and second means in the first position. Thus connectors can be respectively placed in the first and second means, and  
20   the handle turned to actuate the rack and gear means, causing the connectors to be driven toward each other initially rapidly, and then more slowly, with higher mechanical advantage, so that a debilitated person does not have to struggle with the final,  
25   frictional locking of the connectors into their connected relationship. Similarly, breaking of the frictional relationship between the connectors is also easy in this system.

          The teeth of the rack may be positioned at differing  
30   distances from an axis of relative motion, i.e., any axis defining the relative motion between the rack and gear between the first and second positions. These differing distances of the gear teeth of the rack may correspond inversely to the  
35   differing pitches of the gear teeth, to permit relatively linear motion along the axis. Specifically, the sum of the pitch of each gear tooth and the distance from said axis of a rack tooth meshing against such gear tooth may be substantially constant  
40   from gear tooth to gear tooth along the entire length of the rack and gear system as the gear rolls along the rack. The result of this is to permit relatively linear motion of the rack



5 along an axis between the first and second positions, even though the pitches of the gear teeth are variable.

The housing may also define latch means and a latch engaging site, for example an engaging hook and wall, described in  
10 greater detail below, which prevents reopening of the drawer means after initial closing until the second means is moved to the second position.

#### Description of the Drawings

15 In the drawings, Figure 1 is a fragmentary, perspective view of apparatus of this invention, shown to be holding a pair of connectors for use in peritoneal dialysis.

Figure 2 is a fragmentary, perspective view of the apparatus  
20 of Figure 1, showing it in an intermediate configuration of use.

Figure 3 is a fragmentary, perspective view similar to Figure 1, showing the apparatus of this invention after the connection between the connectors has been made and the  
25 antibacterial radiation process has been applied.

Figures 4 and 5 are fragmentary perspective views of the second means and the rack and gear means of this invention, shown in different positions.

30 Figure 6 is a fragmentary, longitudinal sectional view of the apparatus of this invention with the drawer closed.

Figure 7 is a sectional view taken along line 7-7 of Figure 6.

35 Figure 8 is a fragmentary sectional view taken along line 8-8 of Figure 7.

Figure 9 is a fragmentary transverse sectional view of the apparatus of this invention taken along line 9-9.





5     Description of Specific Embodiment

Referring to Figures 1-3, the apparatus 10 of this invention includes housing 12 and a slide drawer 14. A convoluted ultraviolet bulb 16 within housing 12 may define a channel 18 (Figure 10) between the respective convolutions of bulb 16 into which the respective connectors 20, 22 may be placed by closing of drawer 14 for ultraviolet irradiation thereof. Connector 20 may connect to peritoneal transfer set tubing 21, while connector 22 may be a flexible, diaphragm-containing tube carried by peritoneal dialysis solution bag 24.

The design of apparatus 10 including housing 12, drawer 14, and ultraviolet bulb 16 may be generally similar to the design disclosed in the cited Hogan patent, except for the design changes described herein. Also, the housing, drawer, and ultraviolet bulb used in this invention may be generally similar in design except as otherwise indicated herein to the germicidal chamber currently available to the public from Travenol Laboratories, Inc. for irradiating connections in CAPD with ultraviolet radiation.

Connector 22 is positioned within a separable, molded member which comprises shaping sleeve 26 proportioned to receive the flexible end of connector 22 and to shape it as shown in Figure 3 into a desired, circular configuration, to receive the spike 28 of connector 20, puncturing diaphragm 30 in a conventional manner. The molded member containing sleeve 26 also carries hexagonal flange 32, which can fit in first means 34 for holding connector 22, which is shown to be a generally U-shaped trough, receiving flange 32 and holding the structure in position.

The molded member also includes sliding clamp member 36, positioned in a slide box 38, which may be of the general design of analogous structure shown in Lueders et al. U.S. Application



5 Serial No. 338,712, filed January 11, 1982 and entitled  
"CONTINUOUS AMBULATORY PERITONEAL DIALYSIS CLAMPING SYSTEM", to  
serve as a slide clamp to control flow through the flexible  
tubing which comprises connector 22, connected to peritoneal  
10 dialysis solution bag 24.

Second connector 20 is carried by second means 40 for  
holding the connector. Second means 40, as shown by Figures  
4-7, is carried as part of a rack and gear system including rack  
15 42 and gear 44. Rack 42 is attached to and can move with plate  
43, while gear 44 is in a fixed position. Second means 40 is  
shown to be attached to rack 42 and to slide in a track groove  
46 defined by the front panel 48 of drawer 14.

20 Gear 44 rotates about shaft 50, which terminates in handle  
51. As handle 51 is rotated, gear 44 correspondingly rotates,  
to move rack 42 between the respective first and second  
positions illustrated respectively in Figures 1 and 4, and  
25 Figures 3 and 5. Rack and gear systems 42, 44 can be purchased  
from Cunningham Industries of Stamford, Connecticut.

It can be seen that teeth 52 of gear 44 define increasing  
pitch (distance) from the center of each gear tooth 52 to the  
30 center or axis of rotation 54, extending approximately 180°  
about gear 44, so that the pitch or distance of gear tooth 52a  
from center of rotation 54 is much greater than the  
corresponding pitch or distance of gear tooth 52b.

35 It can also be seen that teeth 56 of rack 42 are  
correspondingly not in parallel array with axis of rack movement  
58 between the first and second positions, but are positioned at  
differing distances from axis 58 so that rack tooth 56a is  
40 closer to axis 58 than rack tooth 56b. The spacing from axis 58  
of the respective teeth 56 corresponds inversely to the  
differing pitches of gear teeth 52 so that rack 42 can move in

5 relatively linear motion along axis 58. Specifically, the sum  
of the pitch of each gear tooth 52 and the distance from axis 58  
of a rack tooth 56 meshing against such gear tooth is  
substantially constant. In other words, the sum of the pitch 53  
10 of gear tooth 52a from axis of rotation 54 and the perpendicular  
distance 55 of rack tooth 56a from axis 58 (Figure 4) should be  
substantially equal to the corresponding pitch of gear tooth 52b  
plus the distance from axis 58 of gear tooth 56b. Thus as the  
15 pitch of each gear tooth increases, the perpendicular distance  
of each rack tooth from axis 58 correspondingly decreases. This  
permits substantially linear, perpendicular motion of rack 42  
relative to axis of rotation 54.

20 Drawer 14 is conventionally slidable into and out of housing  
12, taking first means 34 and second means 40 for holding the  
respective connectors with it. As shown, first means 34, the  
U-shaped trough, is open at the top and defined in a side wall  
25 of drawer 14. On the opposite side wall of drawer 14 an open  
slot 60 is provided to receive connector 20 of tubing 21 in  
sliding relation to it. Housing 12 carries horizontal slots to  
intersect the slots defined by first means 34 and slot 60, to  
30 permit closing of drawer 14 with the respective connectors in  
place. The specific design may be similar to the currently  
available Travenol germicidal chamber or the previously cited  
Hogan patent.

35 Turning particularly to Figure 7, drawer 14 is shown to  
carry pivotable latch hook means 66, which is positioned to  
latch against latch wall 68 of housing 12 as the latch engaging  
site (see Figures 1, 3, and 7) for engagement of pivotable latch  
40 hook 66 and latch wall 68 in the first position of second means  
40, i.e., when the connectors are separated, and when the drawer  
means 14 is closed. As shown in Figure 7, latch hook means 66



5 defines an angled face 69 which causes latch hook 66 to deflect  
upwardly as drawer 14 is closed when it impinges latch wall 68.  
As drawer 14 completes the closing action, latch hook 66 falls  
back again as shown in Figure 7, to prevent reopening of the  
10 drawer in that position.

However, as shown in Figures 1 and 3, the latch wall 68 only  
extends across a portion of the width of housing 10, with a  
reduced height wall 70 occupying substantially the remainder of  
15 the width of the housing. Accordingly, as second connector  
holding means 40 is moved by rotation of handle 51 toward the  
first, connected position, latch hook 66 which is carried with  
it is moved out of engagement with latch wall 68, being capable  
20 of passing over the top of reduced height wall 70. Thus drawer  
14 can be opened after closing, when handle 51 is rotated as  
shown in Figure 2 to move second means 40 into the first,  
connected position.

25 Other designs of latch means and latch engaging site may  
also be used.

Referring to Figures 8 and 9, it can be seen that second  
connector holding means 40 defines a pair of slots 72, 74 for  
30 receiving corresponding flanges 751 of a connector 20 as shown  
in Figures 1 and 3. A separate partially cylindrical portion 76  
is also provided, defining spring arm means for releasably  
retaining connector 20. Thus, connector 20 can snap into and  
35 out of retained relationship with second means 40.

For use of the apparatus of this invention, a patient on  
CAPD has typically drained spent dialysis solution from his  
peritoneal cavity through tubing 21 and connector 20 into a bag  
40 24. He then inserts connector 20 into first and second holding  
means 34, 40 with drawer 14 and handle 51 in the position of  
Figure 3. Handle 51 is then rotated to the Figure 1 position,

5 separating connector 20 from connector tubing 22. Bag 24 and  
connector tubing 22 are then replaced with a fresh bag 24 and  
tubing 22, and drawer 14 is closed to begin irradiation. Line  
21 may be closed off with a slide clamp or the like in  
10 conventional manner. The molded structure comprising sleeve 26  
is placed onto port 22 of the fresh bag of dialysis solution 24  
to seat it in the first connector holding means 34 with slide  
clamp 36 being closed.

15 Ultraviolet lamp system 16 is activated by the closing of  
the drawer in a manner which may be similar to the electronic  
system of the Travenol germicidal chamber, with the ultraviolet  
irradiation continuing until the desired level of irradiation is  
20 achieved. This can be signaled to the patient by known  
circuitry, and an indicator light or buzzer, following which the  
patient rotates handle 51 again to the configuration shown in  
Figure 2, causing the respective connectors to connect into flow  
25 relationship with each other. Thereafter, the patient opens  
drawer 14 again as in Figure 3, and removes the newly connected  
system. He then opens clamp 36 and the clamp on tubing 21 to  
cause the fresh peritoneal dialysis solution to flow from bag 24  
30 through tubing 21 into the patient's peritoneal cavity.

As the result of this, even a debilitated patient can make  
connections with ease, and with improved reliability of aseptic  
conditions, with the ultraviolet light irradiation greatly  
35 reducing the risk of contamination and consequent peritonitis.  
The respective parts exposed to ultraviolet light such as spike  
20 and sleeve 26, may be made of known ultraviolet transparent  
materials so that their interiors as well as their exteriors may  
40 be irradiated for antibacterial effect.



- 5        The above has been offered for illustrative purposes only, and is not intended to limit the scope of the invention of this application, which is as defined in the claims below.



5        THAT WHICH IS CLAIMED IS:

10            1. In radiation sterilization apparatus for a pair of  
connectors to be joined together, said connectors being carried  
at the ends of flow conduits, and said apparatus comprising a  
housing, means within said housing for providing antibacterial  
radiation, and first and second means for respectively holding  
said connectors within said housing in a position to be  
irradiated by said radiation, the improvement comprising, in  
15        combination, drawer means carrying said first and second means  
to permit exposure of said connectors to antibacterial radiation  
when said drawer means is closed and to permit manual access to  
said connectors when mounted in said first and second means when  
20        the drawer means is opened, at least one of said first and  
second means being movable by control means operable from  
outside said housing between first and second positions, to  
cause connectors carried in the first and second means to be  
25        separated from each other in the first position, and to cause  
said carried connectors to be joined together in the second  
position.

30            2. The apparatus of Claim 1 in which said means for  
providing radiation is a source of ultraviolet radiation.

35            3. The apparatus of Claim 2 in which said apparatus carries  
a pair of connectors in the first and second means for  
respectively holding said connectors, one of said connectors  
being a port of a peritoneal dialysis solution bag, and the  
other of said connectors being attached to tubing which, in  
turn, connects with the peritoneal cavity of a patient.



4. In apparatus for automatically connecting and disconnecting a pair of connectors, including a housing; means within said housing for providing radiation for antibacterial effect therein; first and second means for respectively holding said connectors, said first and second means being relatively movable between first and second positions, to cause connectors carried in the first and second means to be separated from each other in the first position, and to cause said carried connectors to be joined together in the second position; rack and gear means for relatively moving said first and second means between said first and second positions, the gear of said rack and gear means defining gear teeth of increasing pitch from its center of rotation about at least a portion of its periphery, the rack of said rack and gear means defining mating teeth correspondingly spaced along its length in positions to permit relatively linear motion between said rack and gear as the gear rolls along the rack, whereby the mechanical advantage of the rack and gear means varies with the position of the gear along the rack.

5. The apparatus of Claim 4 in which said mechanical advantage is substantially at its maximum when the rack and gear means are at the second position.

6. The apparatus of Claim 4 in which the teeth of said rack are positioned at differing distances from an axis of relative motion of the first and second means between the first and second positions, said differing distances inversely corresponding to the differing pitches of the gear teeth to permit relatively linear motion along said axis.



5           7. The apparatus of Claim 6 in which the sum of the pitch of each gear tooth and the distance from said axis of a rack tooth meshing against said gear tooth is substantially constant from gear tooth to gear tooth.

10           8. The apparatus of Claim 7 in which said radiation providing means is a source of ultraviolet radiation.

15           9. The apparatus of Claim 7 in which said housing defines drawer means, said drawer means carrying said first and second means to permit exposure of said connector to antibacterial radiation when the drawer means is closed.

20           10. The apparatus of Claim 7 in which one of said housing and second means defines latch means, said second means being movable by the rack and gear means, and the other of said housing and second means defining a latch engaging site positioned to engage said latch means in the first position and to be spaced from the latch means in the second position, 25 whereby said drawer means cannot be reopened after closing until said second means is moved to the second position.

30           11. The apparatus of Claim 7 in which one of said first and second means defines spring arm means for releasably retaining a connector.

35           12. The apparatus of Claim 7 in which said second means for holding the connectors is movable by said rack and gear means between the first and second positions, said gear of the gear means being attached to a rotatable shaft, whereby rotation of such shaft and gear causes said rack to move in a direction



5 transverse of said shaft, said shaft terminating in a rotatable handle.

10 13. The apparatus of Claim 7 in which said shaft carries rotatable handle means adapted to rotate substantially 180° to cause said second means to move between the first and second positions.

15 14. An apparatus for automatically connecting and disconnecting a pair of connectors, including a housing, and means within said housing for providing radiation for antibacterial effect therein; first and second means for respectively holding said connectors, said second means being relatively movable between first and second positions to cause  
20 connectors carried in the first and second means to be separated from each other in the first position and to cause said carried connectors to be joined together in the second position, rack and gear means for relatively moving said first and second means  
25 between said first and second positions, the gear of said rack and gear means defining gear teeth of increasing pitch from its center of rotation about at least a portion of its periphery, the rack of said rack and gear means defining teeth which are  
30 positioned at differing distances from an axis of relative motion of the first and second means between the first and second positions, said differing distances inversely corresponding to the differing pitches of the gear teeth to  
35 permit relatively linear motion along said axis between said rack and gear as the gear rolls along the rack, whereby the mechanical advantage of the rack and gear means varies with the position of the gear along the rack, said mechanical advantage  
40 being substantially at its maximum when the rack and gear means are at the second position.



5           15. The apparatus of Claim 14 in which the sum of the pitch of each gear tooth and the distance from said axis of a rack tooth meshing against said gear tooth is substantially constant from gear tooth to gear tooth.

10           16. The apparatus of Claim 15 in which said radiation providing means is a source of ultraviolet radiation.

15           17. An apparatus for automatically connecting and disconnecting a pair of connectors, including first and second means for respectively holding said connectors, said first and second means being relatively movable between first and second positions to cause connectors carried in the first and second means to be separated from each other in the first position, and  
20           to cause said carried connectors to be joined together in the second position, rack and gear means for relatively moving said first and second means between said first and second positions, the gear of said rack and gear means defining gear teeth of  
25           increasing pitch from its center of rotation about at least a portion of its periphery, the rack of said rack and gear means defining mating teeth correspondingly spaced along its length in positions to permit relatively linear motion between said rack  
30           and gear as the gear rolls along the rack, whereby the mechanical advantage of the rack and gear means varies with the position of the gear along the rack, said apparatus including a housing, and means within said housing for providing radiation  
35           for antibacterial effect therein, said housing defining drawer means, said drawer means carrying said first and second means to permit exposure of said connectors to antibacterial radiation when the drawer means is closed, one of said drawer means and  
40           second means defining latch means, said second means being



5 movable by the rack and gear means, and the other of said drawer  
means and second means defining a latch engaging site positioned  
to engage said latch means in the first position and to be  
10 spaced from the latch means in the second position, whereby said  
drawer means cannot be reopened after closing until said second  
means is moved to the second position.

15 18. The apparatus of Claim 17 in which the mechanical  
advantage of the rack and gear means is substantially at its  
maximum when the rack and gear means are at the second position,  
the teeth of said rack being positioned at differing distances  
from an axis of relative motion of the first and second means  
20 between the first and second positions, said differing distances  
inversely corresponding to the differing pitches of the gear  
teeth to permit relatively linear motion along said axis.

25 19. The apparatus of Claim 18 in which one of said first  
and second means defines spring arm means for releasably  
retaining a connector.

30 20. The apparatus of Claim 19 in which said second means  
for holding the connectors is movable by said rack and gear  
means between the first and second positions, said gear of the  
gear means being attached to a rotatable shaft whereby rotation  
of such shaft and gear causes said rack to move in a direction  
transverse of said shaft, said shaft terminating in a rotatable  
handle.

35 21. The apparatus of Claim 20 in which said shaft carries  
rotatable handle means adapted to rotate substantially 180° to  
cause said second means to move between the first and second  
positions.



5           22. An apparatus for automatically connecting and  
disconnecting a pair of connectors, including a housing; means  
within said housing for providing radiation for antibacterial  
effect therein; first and second means for respectively holding  
10 said containers, said first and second means being relatively  
movable between first and second positions, to cause connectors  
carried in the first and second means to be separated from each  
other in the first position, and to cause said carried  
15 connectors to be joined together in the second position; means  
for relatively moving said first and second means between said  
first and second positions; said housing defining housing, said  
housing carrying said first and second means, to permit exposure  
20 of said connector to antibacterial radiation when the drawer is  
closed and to provide access to said connector when the housing  
is open, said second means being movable by said relatively  
movable means, one of said housing and second means defining  
25 latch means, the other of said housing and second means defining  
a latch engaging site positioned to engage said latch means in  
the first position and to be spaced from the latch means in the  
second position, whereby said housing cannot be reopened after  
30 closing until said second means is moved to the second position.

23. The apparatus of Claim 22 in which said radiation  
providing means is a source of ultraviolet radiation.

35           24. The apparatus of Claim 22 in which said second means  
for holding the connectors is movable by rack and gear means  
between the first and second positions, said gear of the gear  
means being attached to a rotatable shaft, whereby rotation of  
said shaft and gear causes said rack to move in a direction  
40 transverse of said shaft, said shaft terminating in a rotatable  
handle.



- 5        25. The apparatus of Claim 22 in which said shaft and rotatable handle is adapted to rotate substantially 180° to cause said second means to move between the first and second position.






FIG. 1




FIG. 2




FIG. 3





FIG. 5








FIG. 9



# INTERNATIONAL SEARCH REPORT

International Application PCT/US84/00929

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (If several classification symbols apply, indicate all) <sup>3</sup> According to International Patent Classification (IPC) or to both National Classification and IPC INT. CL. A61L 2/10; A61M 31/00 U.S. CL. 250/455.1; 604/29, 283, 905																	
<b>II. FIELDS SEARCHED</b> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; margin: 5px 0;">Minimum Documentation Searched <sup>4</sup></div> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 30%; border-bottom: 1px solid black;">Classification System</th> <th style="border-bottom: 1px solid black;">Classification Symbols</th> </tr> <tr> <td style="padding: 5px; vertical-align: top;">U.S.</td> <td style="padding: 5px; vertical-align: top;">250/455.1 604/29, 244, 283, 411, 905</td> </tr> </table> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; margin: 5px 0;">Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched <sup>5</sup></div>			Classification System	Classification Symbols	U.S.	250/455.1 604/29, 244, 283, 411, 905											
Classification System	Classification Symbols																
U.S.	250/455.1 604/29, 244, 283, 411, 905																
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT</b> <sup>14</sup> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 10%; border-bottom: 1px solid black;">Category <sup>6</sup></th> <th style="width: 70%; border-bottom: 1px solid black;">Citation of Document, <sup>15</sup> with indication, where appropriate, of the relevant passages <sup>17</sup></th> <th style="width: 20%; border-bottom: 1px solid black;">Relevant to Claim No. <sup>18</sup></th> </tr> <tr> <td style="padding: 5px; vertical-align: top;">A, P</td> <td style="padding: 5px; vertical-align: top;">US, A, 4,433,244 Published 21 February 1984</td> <td style="padding: 5px; vertical-align: top;">1-25</td> </tr> <tr> <td style="padding: 5px; vertical-align: top;">A, P</td> <td style="padding: 5px; vertical-align: top;">US, A, 4,439,193 Published 27 March 1984</td> <td style="padding: 5px; vertical-align: top;">1-25</td> </tr> <tr> <td style="padding: 5px; vertical-align: top;">A</td> <td style="padding: 5px; vertical-align: top;">US, A, 4,196,730 Published 08 April 1980, See Col. 12, lines 1-30.</td> <td style="padding: 5px; vertical-align: top;">4-21, 24-25</td> </tr> <tr> <td style="padding: 5px; vertical-align: top;">A</td> <td style="padding: 5px; vertical-align: top;">N, Nephrology Nurse, March/April 1981, Alex E. Zaharias, R.N., CAPD for the Blind, pages 53-54.</td> <td style="padding: 5px; vertical-align: top;">1-25</td> </tr> </table>			Category <sup>6</sup>	Citation of Document, <sup>15</sup> with indication, where appropriate, of the relevant passages <sup>17</sup>	Relevant to Claim No. <sup>18</sup>	A, P	US, A, 4,433,244 Published 21 February 1984	1-25	A, P	US, A, 4,439,193 Published 27 March 1984	1-25	A	US, A, 4,196,730 Published 08 April 1980, See Col. 12, lines 1-30.	4-21, 24-25	A	N, Nephrology Nurse, March/April 1981, Alex E. Zaharias, R.N., CAPD for the Blind, pages 53-54.	1-25
Category <sup>6</sup>	Citation of Document, <sup>15</sup> with indication, where appropriate, of the relevant passages <sup>17</sup>	Relevant to Claim No. <sup>18</sup>															
A, P	US, A, 4,433,244 Published 21 February 1984	1-25															
A, P	US, A, 4,439,193 Published 27 March 1984	1-25															
A	US, A, 4,196,730 Published 08 April 1980, See Col. 12, lines 1-30.	4-21, 24-25															
A	N, Nephrology Nurse, March/April 1981, Alex E. Zaharias, R.N., CAPD for the Blind, pages 53-54.	1-25															
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p><sup>*</sup> Special categories of cited documents: <sup>19</sup></p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 50%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p> </div> </div>																	
<b>IV. CERTIFICATION</b> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border-bottom: 1px solid black; padding: 5px;">Date of the Actual Completion of the International Search <sup>2</sup></td> <td style="width: 50%; border-bottom: 1px solid black; padding: 5px;">Date of Mailing of this International Search Report <sup>3</sup></td> </tr> <tr> <td style="padding: 5px;">09 August 1984</td> <td style="padding: 5px; text-align: center;">23 AUG 1984</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 5px;">International Searching Authority <sup>1</sup></td> <td style="border-bottom: 1px solid black; padding: 5px;">Signature of Authorized Officer <sup>20</sup></td> </tr> <tr> <td style="padding: 5px;">ISA/US</td> <td style="padding: 5px; text-align: center;">             Jack I. Berman         </td> </tr> </table>			Date of the Actual Completion of the International Search <sup>2</sup>	Date of Mailing of this International Search Report <sup>3</sup>	09 August 1984	23 AUG 1984	International Searching Authority <sup>1</sup>	Signature of Authorized Officer <sup>20</sup>	ISA/US	 Jack I. Berman							
Date of the Actual Completion of the International Search <sup>2</sup>	Date of Mailing of this International Search Report <sup>3</sup>																
09 August 1984	23 AUG 1984																
International Searching Authority <sup>1</sup>	Signature of Authorized Officer <sup>20</sup>																
ISA/US	 Jack I. Berman																